

## TYRES

Product group	Tyres
Item number	15715240
Valid tyre size	710 / 50 R 30.5
LI / SI / PR	173 D
TL/TT	TL
Brand	BKT
Tread pattern	Ridemax FL 693 M



## Notes and features

- Steel belted flotation tyre for versatile applications on a wide range of agricultural vehicles and trailers.
- Enormous load capacity and high transport performance due to 65 km/h approval (in some cases even 70 km/h).
- Modern, directional tread pattern for very good road characteristics as well as cleaning properties when used in fields.
- Low rolling resistance allows fuel savings.

## Technical Informations

Item number	15715240
EAN	8903094037049
Valid tyre size	710 / 50 R 30.5
LI / SI / PR	173 D
TL/TT	TL
Brand	BKT
Tread pattern	Ridemax FL 693 M
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	192,71
Recommended rim size	AG24.00
Permitted rim size	AG20.00
Maximum air pressure [bar].	4,00
Section width (mm)	727
Outer diameter of tyre [mm].	1485
Stat. radius (SLR) [mm]	656
Speed Radius Index (SRI)	700
Rolling circumference [mm].	4533
Tread depth (mm)	26,0
Tyre capacity 75% [ltr.]	607
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
173 D	6500	65		4,00	