

TYRES

Product group	Tyres
Item number	15715245
Valid tyre size	750 / 60 R 30.5
LI / SI / PR	181 D
TL/TT	TL
Brand	BKT
Tread pattern	FL 630 Super



Notes and features

- Flotation tyre with steel belt reinforcement for use on slurry tankers, manure spreaders and similar towed agricultural vehicles
- Optimised tread pattern, larger contact area between lugs and ground for smoother driving
- Designed more for use in fields and on arable land
- Extreme puncture resistance

Technical Informations

Item number	15715245
EAN	8903094041190
Valid tyre size	750 / 60 R 30.5
LI / SI / PR	181 D
TL/TT	TL
Brand	BKT
Tread pattern	FL 630 Super
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	232,30
Recommended rim size	AG24.00
Maximum air pressure [bar].	4,00
Section width (mm)	754
Outer diameter of tyre [mm].	1675
Stat. radius (SLR) [mm]	746
Rolling circumference [mm].	5115
Tread depth (mm)	26,0
Tyre capacity 75% [ltr.]	733
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
181 D	8250	65		4,00	