

TYRES

Product group	Tyres
Item number	15715250
Valid tyre size	750 / 60 R 30.5
LI / SI / PR	181 D
TL/TT	TL
Brand	BKT
Tread pattern	Ridemax FL 693 M



Notes and features

- Steel belted flotation tyre for versatile applications on a wide range of agricultural vehicles and trailers.
- Enormous load capacity and high transport performance due to 65 km/h approval (in some cases even 70 km/h).
- Modern, directional tread pattern for very good road characteristics as well as cleaning properties when used in fields.
- Low rolling resistance allows fuel savings.

Technical Informations

Item number	15715250
EAN	8903094033812
Valid tyre size	750 / 60 R 30.5
LI / SI / PR	181 D
TL/TT	TL
Brand	BKT
Tread pattern	Ridemax FL 693 M
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	246,43
Recommended rim size	AG24.00
Maximum air pressure [bar].	4,00
Section width (mm)	754
Outer diameter of tyre [mm].	1675
Stat. radius (SLR) [mm]	728
Rolling circumference [mm].	5092
Tread depth (mm)	26,0
Tyre capacity 75% [ltr.]	736
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
181 D	8250	65		4,00	