

## TYRES

Product group	Tyres
Item number	15715269
Valid tyre size	800 / 60 R 32
LI / SI / PR	185 D
TL/TT	TL
Brand	BKT
Tread pattern	Ridemax FL 690



Bohnenkamp  
Moving Professionals



## Notes and features

- Suitable for manure spreaders, transfer vehicles and other towed agricultural vehicles with approx. 75 % road use.
- Tread pattern design with low rolling resistance for low fuel consumption.
- Rugged casing with steel belt reinforcement provides additional load capacity and protection against punctures.

## Technical Informations

Item number	15715269
EAN	8903094066254
Valid tyre size	800 / 60 R 32
LI / SI / PR	185 D
TL/TT	TL
Brand	BKT
Tread pattern	Ridemax FL 690
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	314,29
Recommended rim size	DH27B
Permitted rim size	DW27B
Maximum air pressure [bar].	4,00
Section width (mm)	800
Outer diameter of tyre [mm].	1800
Stat. radius (SLR) [mm]	817
Rolling circumference [mm].	5454
Tread depth (mm)	31,0
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
185 D	9250	65		4,00	