

## TYRES

Product group	Tyres
Item number	15715650
Valid tyre size	VF 560 / 60 R 22.5
LI / SI / PR	166 D
TL/TT	TL
Brand	BKT
Tread pattern	V-Flexa



## Notes and features

- The BKT V-Flexa is a radial flotation tyre for heavy agricultural trailers.
- The VF technology (Very High Flexion) enables the same load capacity at up to 30% lower inflation pressure compared with a standard tyre of the same size.
- Thanks to the strong, all-steel casing, the tyre is extremely resistant against punctures and other damages.
- Three additional, heavy-duty steel belt inserts and the reinforced sidewall provide excellent performance.

## Technical Informations

Item number	15715650
EAN	8903094066629
Valid tyre size	VF 560 / 60 R 22.5
LI / SI / PR	166 D
TL/TT	TL
Brand	BKT
Tread pattern	V-Flexa
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	146,64
Recommended rim size	AG16.00
Maximum air pressure [bar].	3,20
Section width (mm)	555
Outer diameter of tyre [mm].	1250
Stat. radius (SLR) [mm]	550
Rolling circumference [mm].	3756
Tread depth (mm)	24,5
Number of lugs	21x2
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
166 D	5300	65		3,20	