

TYRES

Product group	Tyres
Item number	15715750
Valid tyre size	VF 600 / 55 R 26.5
LI / SI / PR	167 D
TL/TT	TL
Brand	BKT
Tread pattern	V-Flexa



Notes and features

- The BKT V-Flexa is a radial flotation tyre for heavy agricultural trailers.
- The VF technology (Very High Flexion) enables the same load capacity at up to 30% lower inflation pressure compared with a standard tyre of the same size.
- Thanks to the strong, all-steel casing, the tyre is extremely resistant against punctures and other damages.
- Three additional, heavy-duty steel belt inserts and the reinforced sidewall provide excellent performance.

Technical Informations

Item number	15715750
EAN	8903094063949
Valid tyre size	VF 600 / 55 R 26.5
LI / SI / PR	167 D
TL/TT	TL
Brand	BKT
Tread pattern	V-Flexa
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	160,62
Recommended rim size	AG20.00
Maximum air pressure [bar].	2,80
Section width (mm)	615
Outer diameter of tyre [mm].	1342
Stat. radius (SLR) [mm]	580
Speed Radius Index (SRI)	650
Rolling circumference [mm].	3986
Tread depth (mm)	24,5
Tyre capacity 75% [ltr.]	333.75
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
167 D	5450	65		2,80	