

TYRES

Product group	Tyres	
Item number	15715760	
Valid tyre size	VF 600 / 65 R 26.5	
LI / SI / PR	172 D	
TL/TT	TL	
Brand	BKT	
Tread pattern	V-Flexa	





Notes and features

- The BKT V-Flexa is a radial flotation tyre for heavy agricultural trailers.
- The VF technolgy (Very High Flexion) enables the same load capacity at up to 30% lower inflation pressure compared with a standard tyre of the same size.
- Thanks to the strong, all-steel casing, the tyre is extremely resistant against punctures and and other damages.
- Three additional, heavy-duty steel belt inserts and the reinforced sidewall provide excellent performance.



Technical Informations

Item number	15715760
EAN	8903094066056
Valid tyre size	VF 600 / 65 R 26.5
LI / SI / PR	172 D
TL/TT	TL
Brand	BKT
Tread pattern	V-Flexa
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	189,22
Recommended rim size	AG20.00
Maximum air pressure [bar].	2,80
Section width (mm)	615
Outer diameter of tyre [mm].	1453
Stat. radius (SLR) [mm]	628
Rolling circumference [mm].	4377
Tread depth (mm)	24,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
172 D	6300	65		2,80	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.