

TYRES

Product group	Tyres
Item number	15717148
Valid tyre size	IF 240 / 80 R 15
LI / SI / PR	129 D
TL/TT	TL
Brand	BKT
Tread pattern	Rib 713



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- Modern implement tyre designed with latest IF technology for trailers and other agricultural machinery.
- Provides higher load capacities at standard inflation pressure.
- Approved for a maximum speed of 65 km/h.
- Improved puncture resistance thanks to thanks to integrated steel bands.

Technical Informations

Item number	15717148
EAN	8903094047925
Valid tyre size	IF 240 / 80 R 15
LI / SI / PR	129 D
TL/TT	TL
Brand	BKT
Tread pattern	Rib 713
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	23,60
Recommended rim size	8
Maximum air pressure [bar].	5,00
Section width (mm)	240
Outer diameter of tyre [mm].	765
Stat. radius (SLR) [mm]	354
Rolling circumference [mm].	2324
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
129 D	1850	65		5,00	