

TYRES

Product group	Tyres
Item number	15717160
Valid tyre size	31 X 15.50 R 15
LI / SI / PR	122 B
TL/TT	TL
Brand	BKT
Tread pattern	AS 511



Notes and features

- The BKT AS 511 is an implement radial tyre for use on grasslands
- Its tractor tread provides very good self-cleaning properties and traction even on sloping terrains
- Its strong, low-wear rubber compound guarantees a long service life

Technical Informations

Item number	15717160
EAN	8903094059782
Valid tyre size	31 X 15.50 R 15
LI / SI / PR	122 B
TL/TT	TL
Brand	BKT
Tread pattern	AS 511
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	30,26
Recommended rim size	13LB
Permitted rim size	13.00
Maximum air pressure [bar].	2,80
Section width (mm)	388
Outer diameter of tyre [mm].	785
Stat. radius (SLR) [mm]	353
Speed Radius Index (SRI)	380
Rolling circumference [mm].	2387
Tread depth (mm)	18,5
Number of lugs	18x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
122 B	1500	50		2,80	