

TYRES

Product group	Tyres	
Item number	15717164	
Valid tyre size	260 / 70 R 15.3	
LI / SI / PR	134 A8	
TL/TT	TL	
Brand	ВКТ	
Tread pattern	AW 712	





Notes and features

- The BKT 712 is a radial implement tyre for slurry tanks and other agricultural trailers
- Thanks to the strong casing and the stubble-resistant rubber compound, the tyre is extremely durable
- The special tread pattern also provides excellent ride comfort.



Technical Informations

Item number	15717164
EAN	8903094059584
Valid tyre size	260 / 70 R 15.3
LI / SI / PR	134 A8
TL/TT	TL
Brand	BKT
Tread pattern	AW 712
Carcass properties	Stubble Resistant
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	24,07
Recommended rim size	9.00
Maximum air pressure [bar].	6,00
Section width (mm)	264
Outer diameter of tyre [mm].	760
Stat. radius (SLR) [mm]	344
Rolling circumference [mm].	2304
Tread depth (mm)	9,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
134 A8	2120	40		6,00	
	2120	50		6,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.