

TYRES

Product group	Tyres	
Item number	15717188	
Valid tyre size	305 / 70 R 16.5	
LI / SI / PR	148 A8 / 148 B	
TL/TT	TL	
Brand	ВКТ	
Tread pattern	AW 711	





Notes and features

- Modern implement tyre for trailers and other agricultural machines for various applications
- Can be mounted tubeless

- Rounded tyre shoulder to protect crops and soil
- Approved up to 50 km/h, low rolling resistance



Technical Informations

Item number	15717188
EAN	8903094053506
Valid tyre size	305 / 70 R 16.5
Alternative size 1	12R16.5
LI / SI / PR	148 A8 / 148 B
TL/TT	TL
Brand	BKT
Tread pattern	AW 711
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	34,85
Recommended rim size	9.75
Maximum air pressure [bar].	5,00
Section width (mm)	325
Outer diameter of tyre [mm].	851
Stat. radius (SLR) [mm]	371
Rolling circumference [mm].	2552
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
148 A8	3150	40		5,00	
148 B	3150	50		5,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.