

TYRES

Product group	Tyres
Item number	15717190
Valid tyre size	340 / 60 R 16.5
LI / SI / PR	145 A8 / 145 B
TL/TT	TL
Brand	BKT
Tread pattern	AW 711



Notes and features

- Modern implement tyre for trailers and other agricultural machines for various applications
- Can be mounted tubeless
- Rounded tyre shoulder to protect crops and soil
- Approved up to 50 km/h, low rolling resistance

Technical Informations

Item number	15717190
EAN	8903094044788
Valid tyre size	340 / 60 R 16.5
LI / SI / PR	145 A8 / 145 B
TL/TT	TL
Brand	BKT
Tread pattern	AW 711
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	37,67
Recommended rim size	11
Permitted rim size	12
Maximum air pressure [bar].	5,00
Section width (mm)	324
Outer diameter of tyre [mm].	820
Stat. radius (SLR) [mm]	368
Rolling circumference [mm].	2476
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
145 A8	2900	40		5,00	
145 B	2900	50		5,00	