

TYRES

| | |
|-----------------|-----------------|
| Product group | Tyres |
| Item number | 15717192 |
| Valid tyre size | 395 / 55 R 16.5 |
| LI / SI / PR | 152 A8 / 152 B |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | AW 711 |



Notes and features

- Modern implement tyre for trailers and other agricultural machines for various applications
- Can be mounted tubeless
- Rounded tyre shoulder to protect crops and soil
- Approved up to 50 km/h, low rolling resistance

Technical Informations

| | |
|------------------------------|-----------------|
| Item number | 15717192 |
| EAN | 8903094053469 |
| Valid tyre size | 395 / 55 R 16.5 |
| LI / SI / PR | 152 A8 / 152 B |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | AW 711 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 41,60 |
| Recommended rim size | 12 |
| Maximum air pressure [bar]. | 5,00 |
| Section width (mm) | 394 |
| Outer diameter of tyre [mm]. | 838 |
| Stat. radius (SLR) [mm] | 365 |
| Rolling circumference [mm]. | 2516 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 152 A8 | 3550 | 40 | | 5,00 | |
| 152 B | 3550 | 50 | | 5,00 | |