

## TYRES

Product group	Tyres
Item number	15717218
Valid tyre size	425 / 55 R 17
LI / SI / PR	140 A8 / 129 D
TL/TT	TL
Brand	BKT
Tread pattern	Ridemax FL 693 M



## Notes and features

- Steel belted flotation tyre for versatile applications on a wide range of agricultural vehicles and trailers.
- Enormous load capacity and high transport performance due to 65 km/h approval (in some cases even 70 km/h).
- Modern, directional tread pattern for very good road characteristics as well as cleaning properties when used in fields.
- Low rolling resistance allows fuel savings.

## Technical Informations

Item number	15717218
EAN	8903094059324
Valid tyre size	425 / 55 R 17
LI / SI / PR	140 A8 / 129 D
TL/TT	TL
Brand	BKT
Tread pattern	Ridemax FL 693 M
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	47,84
Recommended rim size	13.00
Maximum air pressure [bar].	4,00
Section width (mm)	420
Outer diameter of tyre [mm].	894
Stat. radius (SLR) [mm]	397
Rolling circumference [mm].	2704
Tread depth (mm)	14,5
Number of lugs	14x2
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
140 A8	2500	40		4,00	
129 D	1850	65		4,00	