

TYRES

Product group	Tyres	
Item number	15717220	
Valid tyre size	440 / 50 R 17	
LI / SI / PR	135 D	
TL/TT	TL	
Brand	ВКТ	
Tread pattern	Trac Super	





Notes and features

- Radial traction tyre specifically designed for operations on grassland, as well as for mixed on-road and off-road use.
- Aggressive, offset traction tread pattern offers reliable traction in all conditions, especially on slopes.
- Large contact area provides additional stability in use.
- Steel-belt reinforced casing makes the tyre even more stable and protects against punctures.



Technical Informations

Item number	15717220
EAN	8903094038534
Valid tyre size	440 / 50 R 17
LI / SI / PR	135 D
TL/TT	TL
Brand	BKT
Tread pattern	Trac Super
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	51,08
Recommended rim size	14.00
Permitted rim size	13.00
Maximum air pressure [bar].	3,60
Section width (mm)	441
Outer diameter of tyre [mm].	872
Stat. radius (SLR) [mm]	395
Rolling circumference [mm].	2674
Tread depth (mm)	22,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
135 D	2180	65		3,60	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.