

TYRES

Product group	Tyres	
Item number	15717225	
Valid tyre size	VF 480 / 45 R 17	
LI / SI / PR	167 A8 / 167 B	
TL/TT	TL	
Brand	BKT	
Tread pattern	AW 711	





Notes and features

- Modern implement tyre for trailers and other agricultural machines for various applications
- Can be mounted tubeless

- Rounded tyre shoulder to protect crops and soil
- Approved up to 50 km/h, low rolling resistance



Technical Informations

Item number	15717225
EAN	8903094051434
Valid tyre size	VF 480 / 45 R 17
Alternative size 1	19.0/45R17
LI / SI / PR	167 A8 / 167 B
TL/TT	TL
Brand	BKT
Tread pattern	AW 711
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	53,95
Recommended rim size	16.00
Maximum air pressure [bar].	5,00
Section width (mm)	491
Outer diameter of tyre [mm].	866
Stat. radius (SLR) [mm]	363
Rolling circumference [mm].	2644
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
167 A8	5450	50		5,00	
167 B	5450	50		5,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.