

TYRES

Product group	Tyres
Item number	15717230
Valid tyre size	500 / 50 R 17
LI / SI / PR	149 D / 146 E
TL/TT	TL
Brand	BKT
Tread pattern	Ridemax FL 693 M



Notes and features

- Steel belted flotation tyre for versatile applications on a wide range of agricultural vehicles and trailers.
- Enormous load capacity and high transport performance due to 65 km/h approval (in some cases even 70 km/h).
- Modern, directional tread pattern for very good road characteristics as well as cleaning properties when used in fields.
- Low rolling resistance allows fuel savings.

Technical Informations

Item number	15717230
EAN	8903094045181
Valid tyre size	500 / 50 R 17
LI / SI / PR	149 D / 146 E
TL/TT	TL
Brand	BKT
Tread pattern	Ridemax FL 693 M
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	57,42
Recommended rim size	16.00
Maximum air pressure [bar].	5,00
Section width (mm)	503
Outer diameter of tyre [mm].	932
Stat. radius (SLR) [mm]	424
Rolling circumference [mm].	2913
Tread depth (mm)	15,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
149 D	3250	65		5,00	
146 E	3000	70		5,00	