

TYRES

Product group	Tyres
Item number	15717280
Valid tyre size	IF 340 / 65 R 18
LI / SI / PR	153 A8 / 153 B
TL/TT	TL
Brand	BKT
Tread pattern	AW 711



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- Modern implement tyre for trailers and other agricultural machines for various applications
- Can be mounted tubeless
- Rounded tyre shoulder to protect crops and soil
- Approved up to 50 km/h, low rolling resistance

Technical Informations

Item number	15717280
EAN	8903094053476
Valid tyre size	IF 340 / 65 R 18
LI / SI / PR	153 A8 / 153 B
TL/TT	TL
Brand	BKT
Tread pattern	AW 711
Carcass properties	Stubble Resistant
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	36,25
Recommended rim size	W11
Maximum air pressure [bar].	4,00
Section width (mm)	330
Outer diameter of tyre [mm].	899
Stat. radius (SLR) [mm]	381
Rolling circumference [mm].	2662
Tread depth (mm)	9,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
153 A8	3650	40		4,00	
153 B	3650	50		4,00	