

TYRES

Product group	Tyres
Item number	15717292
Valid tyre size	440 / 55 R 18
LI / SI / PR	159 A8 / 159 B
TL/TT	TL
Brand	BKT
Tread pattern	AW 711



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- Modern implement tyre for trailers and other agricultural machines for various applications
- Can be mounted tubeless
- Rounded tyre shoulder to protect crops and soil
- Approved up to 50 km/h, low rolling resistance

Technical Informations

Item number	15717292
EAN	8903094044924
Valid tyre size	440 / 55 R 18
LI / SI / PR	159 A8 / 159 B
TL/TT	TL
Brand	BKT
Tread pattern	AW 711
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	54,00
Recommended rim size	14
Permitted rim size	13
Maximum air pressure [bar].	5,00
Section width (mm)	410
Outer diameter of tyre [mm].	945
Stat. radius (SLR) [mm]	432
Rolling circumference [mm].	2893
Tread depth (mm)	9,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
159 A8	4375	40		5,00	
159 B	4375	50		5,00	