

## TYRES

Product group	Tyres
Item number	15717300
Valid tyre size	24 R 20.5
LI / SI / PR	176 F, 16 PR
TL/TT	TL
Brand	BKT
Tread pattern	Ridemax FL 699



## Notes and features

- The BKT Ridemax FL 699 is a radial tyre for agricultural trailers and tankers used mainly for road transport.
- The tyre enables high loading capacities, good driving control and ride comfort.
- The all-steel casing and reinforced bead provide excellent stability and a long service life.
- The tyre also performs superbly in field applications.

## Technical Informations

Item number	15717300
EAN	8903094063680
Valid tyre size	24 R 20.5
LI / SI / PR	176 F, 16 PR
TL/TT	TL
Brand	BKT
Tread pattern	Ridemax FL 699
Carcass properties	All-Steel
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54
Nettogewicht [kg] (gültig)	192,99
Recommended rim size	18.00
Maximum air pressure [bar].	6,00
Section width (mm)	590
Outer diameter of tyre [mm].	1370
Stat. radius (SLR) [mm]	613
Rolling circumference [mm].	4165
Tread depth (mm)	18,0
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
176 F	7100	80		6,00	