Bohnenkamp Moving Professionals

TYRES

Product group	Tyres	
Item number	15721050	
Valid tyre size	5.50 - 16	
LI / SI / PR	86 A6 / 78 A8, 6 PR	
TL/TT	тт	
Brand	ВКТ	
Tread pattern	TF 8181	



Notes and features

- Agricultural front tyre. .
- Wider tread pattern surface for longer service life.
- Double rib gives greater stiffness. •

Bohnenkamp Moving Professionals

Technical Informations

the second second	45704050
Item number	15721050
EAN	8903094020577
Valid tyre size	5.50 - 16
LI / SI / PR	86 A6 / 78 A8, 6 PR
TL/TT	TT
Brand	ВКТ
Tread pattern	TF 8181
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	8,30
Recommended rim size	4.00E
Permitted rim size	3.50D, 4.50E
Maximum air pressure [bar].	3,70
Section width (mm)	158
Outer diameter of tyre [mm].	720
Stat. radius (SLR) [mm]	340
Rolling circumference [mm].	2145
Tread depth (mm)	13,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
86 A6	530	30		3,70	
78 A8	425	40		3,70	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.