

## **TYRES**

Product group	Tyres	
Item number	15721095	
Valid tyre size	6.00 - 16	
LI / SI / PR	88 A6 / 80 A8, 6 PR	
TL/TT	тт	
Brand	ВКТ	
Tread pattern	TF 8181	



## **Notes and features**

- Agricultural front tyre.
- Wider tread pattern surface for longer service life.
- Double rib gives greater stiffness.



## **Technical Informations**

Item number	15721095
EAN	8903094020584
Valid tyre size	6.00 - 16
LI / SI / PR	88 A6 / 80 A8, 6 PR
TL/TT	тт
Brand	BKT
Tread pattern	TF 8181
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	9,70
Recommended rim size	4.50E
Permitted rim size	4.00E, 5K, 5.00F
Maximum air pressure [bar].	3,30
Section width (mm)	170
Outer diameter of tyre [mm].	745
Stat. radius (SLR) [mm]	350
Rolling circumference [mm].	2220
Tread depth (mm)	15,0
E-Ready	No

## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
88 A6	560	30		3,30	
80 A8	450	40		3,30	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.