Bohnenkamp Moving Professionals

TYRES

Product group	Tyres	
Item number	15721097	
Valid tyre size	6.00 - 16	
LI / SI / PR	94 A6 / 87 A8, 8 PR	
TL/TT	TT	
Brand	ВКТ	
Tread pattern	TF 8181	



Notes and features

- Agricultural front tyre. •
- Wider tread pattern surface for longer service life.
- Double rib gives greater stiffness. •

Bohnenkamp Moving Professionals

Technical Informations

the second second	45704007
Item number	15721097
EAN	8903094020591
Valid tyre size	6.00 - 16
LI / SI / PR	94 A6 / 87 A8, 8 PR
TL/TT	TT
Brand	ВКТ
Tread pattern	TF 8181
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	11,39
Recommended rim size	4.50
Permitted rim size	4.00, 5, 5.00
Maximum air pressure [bar].	4,50
Section width (mm)	170
Outer diameter of tyre [mm].	745
Stat. radius (SLR) [mm]	350
Rolling circumference [mm].	2220
Tread depth (mm)	14,7
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
94 A6	670	30		4,50	
87 A8	545	40		4,50	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.