

TYRES

Product group	Tyres
Item number	15721105
Valid tyre size	6.50 - 16
LI / SI / PR	91 A6 / 83 A8, 6 PR
TL/TT	TT
Brand	BKT
Tread pattern	TF 9090



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- Agricultural front tyre.
- Easy steering.
- Directional stability on wet ground.

Technical Informations

Item number	15721105
EAN	8903094021024
Valid tyre size	6.50 - 16
LI / SI / PR	91 A6 / 83 A8, 6 PR
TL/TT	TT
Brand	BKT
Tread pattern	TF 9090
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	10,90
Recommended rim size	4.50E
Permitted rim size	4.00E, 5K, 5.00F, 5.50F
Maximum air pressure [bar].	3,10
Section width (mm)	180
Outer diameter of tyre [mm].	765
Stat. radius (SLR) [mm]	359
Rolling circumference [mm].	2280
Tread depth (mm)	19,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
91 A6	615	30		3,10	
83 A8	487	40		3,10	