

TYRES

Product group	Tyres
Item number	15721115
Valid tyre size	7.50 - 16
LI / SI / PR	103 A6 / 96 A8, 8 PR
TL/TT	TT
Brand	BKT
Tread pattern	TF 9090



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- Agricultural front tyre.
- Easy steering.
- Directional stability on wet ground.

Technical Informations

Item number	15721115
EAN	8903094021123
Valid tyre size	7.50 - 16
LI / SI / PR	103 A6 / 96 A8, 8 PR
TL/TT	TT
Brand	BKT
Tread pattern	TF 9090
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	16,04
Recommended rim size	5.50F
Permitted rim size	5.00F, 5K, 6.00F
Maximum air pressure [bar].	3,70
Section width (mm)	207
Outer diameter of tyre [mm].	810
Stat. radius (SLR) [mm]	379
Rolling circumference [mm].	2414
Tread depth (mm)	21,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
103 A6	875	30		3,70	
96 A8	710	40		3,70	