

TYRES

Product group	Tyres	
Item number	15721130	
Valid tyre size	9.00 - 16	
LI / SI / PR	116 A6 / 108 A8, 10 PR	
TL/TT	тт	
Brand	ВКТ	
Tread pattern	TF 9090	





Notes and features

- Agricultural front tyre.
- Easy steering.

• Directional stability on wet ground.



Technical Informations

Item number	15721130
EAN	8903094021338
Valid tyre size	9.00 - 16
LI / SI / PR	116 A6 / 108 A8, 10 PR
TL/TT	тт
Brand	BKT
Tread pattern	TF 9090
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	23,50
Recommended rim size	8
Permitted rim size	6.00F, 7, 8L
Maximum air pressure [bar].	3,90
Section width (mm)	257
Outer diameter of tyre [mm].	855
Stat. radius (SLR) [mm]	398
Rolling circumference [mm].	2548
Tread depth (mm)	25,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
116 A6	1250	30		3,90	
108 A8	1000	40		3,90	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.