Bohnenkamp Moving Professionals

TYRES

Product group	Tyres
Item number	15721160
Valid tyre size	11.00 - 16
LI / SI / PR	118 A6 / 110 A8, 8 PR
TL/TT	тт
Brand	ВКТ
Tread pattern	TF 8181



Notes and features

- Agricultural front tyre. •
- Wider tread pattern surface for longer service life.
- Double rib gives greater stiffness. •

Bohnenkamp Moving Professionals

Technical Informations

	45704400
Item number	15721160
EAN	8903094032761
Valid tyre size	11.00 - 16
LI / SI / PR	118 A6 / 110 A8, 8 PR
TL/TT	TT
Brand	ВКТ
Tread pattern	TF 8181
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	35,91
Recommended rim size	10L
Permitted rim size	8, 8L
Maximum air pressure [bar].	2,50
Section width (mm)	326
Outer diameter of tyre [mm].	980
Stat. radius (SLR) [mm]	447
Rolling circumference [mm].	2920
Tread depth (mm)	28,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
118 A6	1320	30		2,50	
110 A8	1060	40		2,50	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.