Bohnenkamp Moving Professionals

TYRES

Product group	Tyres
Item number	15721190
Valid tyre size	6.00 - 18
LI / SI / PR	101 A6 / 94 A8, 8 PR
TL/TT	ТТ
Brand	ВКТ
Tread pattern	TF 8181



Notes and features

- Agricultural front tyre.
- Wider tread pattern surface for longer service life.
- Double rib gives greater stiffness.

Bohnenkamp Moving Professionals

Technical Informations

Item number	15721190
EAN	8903094055807
Valid tyre size	6.00 - 18
LI / SI / PR	101 A6 / 94 A8, 8 PR
TL/TT	ТТ
Brand	ВКТ
Tread pattern	TF 8181
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	13,35
Recommended rim size	4.50
Maximum air pressure [bar].	4,20
Section width (mm)	172
Outer diameter of tyre [mm].	800
Stat. radius (SLR) [mm]	374
Rolling circumference [mm].	2410
Tread depth (mm)	11,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
101 A6	825	30		4,20	
94 A8	670	40		4,20	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.