

TYRES

Product group	Tyres	
Item number	15721200	
Valid tyre size	7.50 - 18	
LI / SI / PR	106 A6 / 96 A8, 8 PR	
TL/TT	тт	
Brand	BKT	
Tread pattern	TF 9090	





Notes and features

- Agricultural front tyre.
- Easy steering.

• Directional stability on wet ground.



Technical Informations

Item number	15721200
EAN	8903094021192
Valid tyre size	7.50 - 18
LI / SI / PR	106 A6 / 96 A8, 8 PR
TL/TT	ТТ
Brand	BKT
Tread pattern	TF 9090
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	17,53
Recommended rim size	5.50F
Maximum air pressure [bar].	3,70
Section width (mm)	207
Outer diameter of tyre [mm].	860
Stat. radius (SLR) [mm]	404
Rolling circumference [mm].	2562
Tread depth (mm)	21,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
106 A6	950	30		3,70	
96 A8	710	40		3,70	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.