

## **TYRES**

Product group	Tyres	
Item number	15721255	
Valid tyre size	7.50 - 20	
LI / SI / PR	103 A6 / 96 A8, 6 PR	
TL/TT	тт	
Brand	BKT	
Tread pattern	TF 8181	



## **Notes and features**

- Agricultural front tyre.
- Wider tread pattern surface for longer service life.
- Double rib gives greater stiffness.



## **Technical Informations**

Item number	15721255
EAN	8903094020683
Valid tyre size	7.50 - 20
LI / SI / PR	103 A6 / 96 A8, 6 PR
TL/TT	тт
Brand	BKT
Tread pattern	TF 8181
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	18,05
Recommended rim size	5.50F
Permitted rim size	5.00F
Maximum air pressure [bar].	2,80
Section width (mm)	205
Outer diameter of tyre [mm].	915
Stat. radius (SLR) [mm]	431
Rolling circumference [mm].	2725
Tread depth (mm)	21,0
E-Ready	No

## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
103 A6	875	30		2,80	
96 A8	710	40		2,80	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.