

TYRES

Product group	Tyres
Item number	15721350
Valid tyre size	6.00 - 16
LI / SI / PR	94 A6 / 87 A8, 8 PR
TL/TT	тт
Brand	ВКТ
Tread pattern	Steer Farm





Notes and features

• The BKT Steer Farm is a front tyre for tractors.

• Its typical front tread offers very good steering response.



Technical Informations

Item number	15721350
EAN	8903094030842
Valid tyre size	6.00 - 16
LI / SI / PR	94 A6 / 87 A8, 8 PR
TL/TT	тт
Brand	BKT
Tread pattern	Steer Farm
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	11,89
Recommended rim size	4.50E
Permitted rim size	4.00E, 5K, 5.00F
Maximum air pressure [bar].	4,50
Section width (mm)	170
Outer diameter of tyre [mm].	740
Stat. radius (SLR) [mm]	353
Rolling circumference [mm].	2279
Tread depth (mm)	18,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
94 A6	670	30		4,50	
87 A8	545	40		4,50	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.