

TYRES

Product group	Tyres
Item number	15721405
Valid tyre size	11 L - 15 SL
LI / SI / PR	106 A8, 8 PR
TL/TT	TL
Brand	BKT
Tread pattern	Pro Rib F2M



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- The BKT Pro Rib F2M is a tyre designed for front-wheel use on smaller tractors in soil tillage applications.
- Especially suitable for all applications that require outstanding handling properties.
- Thanks to its high flotation capability, the tyre helps reduce soil compaction.

Technical Informations

Item number	15721405
EAN	8903094020461
Valid tyre size	11 L - 15 SL
LI / SI / PR	106 A8, 8 PR
TL/TT	TL
Brand	BKT
Tread pattern	Pro Rib F2M
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	22,58
Recommended rim size	8LB
Permitted rim size	10LB
Maximum air pressure [bar].	3,00
Section width (mm)	280
Outer diameter of tyre [mm].	795
Stat. radius (SLR) [mm]	370
Rolling circumference [mm].	2370
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
106 A8	950	40		3,00	