

TYRES

| Product group | Tyres | |
|-----------------|---------------|--|
| Item number | 15721415 | |
| Valid tyre size | 10.00 - 16 SL | |
| LI / SI / PR | 110 A8, 8 PR | |
| TL/TT | тт | |
| Brand | BKT | |
| Tread pattern | Pro Rib F2M | |





Notes and features

- The BKT Pro Rib F2M is a tyre designed for front-wheel use on smaller tractors in soil tillage applications.
- Especially suitable for all applications that require outstanding handling properties.
- Thanks to its high flotation capability, the tyre helps reduce soil compaction.



Technical Informations

| Item number | 15721415 |
|------------------------------|---------------|
| EAN | 8903094020447 |
| Valid tyre size | 10.00 - 16 SL |
| LI / SI / PR | 110 A8, 8 PR |
| TL/TT | тт |
| Brand | BKT |
| Tread pattern | Pro Rib F2M |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 22,49 |
| Recommended rim size | 8 |
| Maximum air pressure [bar]. | 3,00 |
| Section width (mm) | 280 |
| Outer diameter of tyre [mm]. | 880 |
| Stat. radius (SLR) [mm] | 409 |
| Rolling circumference [mm]. | 2620 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|-----------------------------|--------------|
| 110 A8 | 1060 | 40 | | 3,00 | |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.