

TYRES

Product group	Tyres
Item number	15721420
Valid tyre size	11.00 - 16 SL
LI / SI / PR	114 A8, 8 PR
TL/TT	TT
Brand	BKT
Tread pattern	Pro Rib F2M



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- The BKT Pro Rib F2M is a tyre designed for front-wheel use on smaller tractors in soil tillage applications.
- Especially suitable for all applications that require outstanding handling properties.
- Thanks to its high flotation capability, the tyre helps reduce soil compaction.

Technical Informations

Item number	15721420
EAN	8903094020454
Valid tyre size	11.00 - 16 SL
LI / SI / PR	114 A8, 8 PR
TL/TT	TT
Brand	BKT
Tread pattern	Pro Rib F2M
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	29,71
Recommended rim size	10LB
Permitted rim size	W8L, 8LB
Maximum air pressure [bar].	2,80
Section width (mm)	335
Outer diameter of tyre [mm].	950
Stat. radius (SLR) [mm]	440
Rolling circumference [mm].	2830
Tread depth (mm)	23,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
114 A8	1180	40		2,80	