

TYRES

Product group	Tyres
Item number	15722040
Valid tyre size	9.5 - 16
LI / SI / PR	96 A6 / 92 A8, 6 PR
TL/TT	TT
Brand	BKT
Tread pattern	TR 171



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- Suitable for wet surfaces.
- Extra high lugs for long service life.
- Very good traction and self-cleaning.

Technical Informations

Item number	15722040
EAN	8903094040506
Valid tyre size	9.5 - 16
LI / SI / PR	96 A6 / 92 A8, 6 PR
TL/TT	TT
Brand	BKT
Tread pattern	TR 171
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	24,82
Recommended rim size	W8L
Permitted rim size	8LB
Maximum air pressure [bar].	2,10
Section width (mm)	241
Outer diameter of tyre [mm].	845
Stat. radius (SLR) [mm]	395
Rolling circumference [mm].	2607
Tread depth (mm)	44,5
Number of lugs	12x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
96 A6	710	30		2,10	
92 A8	630	40		2,10	