Bohnenkamp Moving Professionals

16.11.2024

TYRES

Product group	Tyres	
Item number	15722043	
Valid tyre size	9.5 - 16	
LI / SI / PR	96 A6 / 92 A8, 6 PR	
TL/TT	TT	
Brand	ВКТ	
Tread pattern	TR 144	



Notes and features

- Agricultural bias tyre for smaller tractors. .
- Wide lug spaces for good traction on wet surfaces.
- Angled lugs in the centre for better ride comfort. •

Bohnenkamp Moving Professionals

Technical Informations

Item number	15722043
EAN	8903094041374
Valid tyre size	9.5 - 16
LI / SI / PR	96 A6 / 92 A8, 6 PR
TL/TT	тт
Brand	ВКТ
Tread pattern	TR 144
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	19,98
Recommended rim size	W8L
Permitted rim size	8LB
Maximum air pressure [bar].	2,10
Section width (mm)	245
Outer diameter of tyre [mm].	850
Stat. radius (SLR) [mm]	388
Rolling circumference [mm].	2558
Tread depth (mm)	27,5
Number of lugs	12x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
96 A6	710	30		2,10	
92 A8	630	40		2,10	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.