

## TYRES

Product group	Tyres
Item number	15722049
Valid tyre size	12.4 - 16
LI / SI / PR	97 A6 / 93 A893, 4 PR
TL/TT	TT
Brand	BKT
Tread pattern	TR 135



Bohnenkamp  
■ ■ ● Moving Professionals

**BKT**  
GROWING TOGETHER

## Notes and features

- The BKT TR 135 is an agricultural bias tyre for soil tillage and spraying applications.
- Some sizes and versions are suitable for use on excavators, trailers or harvesters.
- The double angled lugs provide excellent traction.
- The tyre offers good self-cleaning properties and excellent stability, even on difficult ground conditions.
- The lugs overlapping in the tread centre ensure comfortable handling on the road.

## Technical Informations

Item number	15722049
EAN	8903094063444
Valid tyre size	12.4 - 16
LI / SI / PR	97 A6 / 93 A893, 4 PR
TL/TT	TT
Brand	BKT
Tread pattern	TR 135
TRA Code	R1
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	30,06
Recommended rim size	W11
Permitted rim size	W9, W10
Maximum air pressure [bar].	1,20
Section width (mm)	326
Outer diameter of tyre [mm].	960
Stat. radius (SLR) [mm]	431
Rolling circumference [mm].	2852
Tread depth (mm)	33,5
Number of lugs	15x2
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
97 A6	730	30		1,20	
93 A8	650	40		1,20	