

TYRES

Product group	Tyres
Item number	15722060
Valid tyre size	8.3 - 20
LI / SI / PR	96 A6 / 92 A8, 6 PR
TL/TT	TT
Brand	BKT
Tread pattern	TR 144



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- Agricultural bias tyre for smaller tractors.
- Wide lug spaces for good traction on wet surfaces.
- Angled lugs in the centre for better ride comfort.

Technical Informations

Item number	15722060
EAN	8903094004713
Valid tyre size	8.3 - 20
LI / SI / PR	96 A6 / 92 A8, 6 PR
TL/TT	TT
Brand	BKT
Tread pattern	TR 144
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	18,28
Recommended rim size	W7
Permitted rim size	W6
Maximum air pressure [bar].	2,40
Section width (mm)	211
Outer diameter of tyre [mm].	890
Stat. radius (SLR) [mm]	414
Rolling circumference [mm].	2670
Tread depth (mm)	28,0
Number of lugs	17x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
96 A6	710	30		2,40	
92 A8	630	40		2,40	