

## TYRES

Product group	Tyres
Item number	15722077
Valid tyre size	12.4 - 20
LI / SI / PR	116 A6 / 112 A8, 8 PR
TL/TT	TT
Brand	BKT
Tread pattern	TR 135



Bohnenkamp  
■ ■ ● Moving Professionals

**BKT**  
GROWING TOGETHER

## Notes and features

- The BKT TR 135 is an agricultural bias tyre for soil tillage and spraying applications.
- Some sizes and versions are suitable for use on excavators, trailers or harvesters.
- The double angled lugs provide excellent traction.
- The tyre offers good self-cleaning properties and excellent stability, even on difficult ground conditions.
- The lugs overlapping in the tread centre ensure comfortable handling on the road.

## Technical Informations

Item number	15722077
EAN	8903094028825
Valid tyre size	12.4 - 20
LI / SI / PR	116 A6 / 112 A8, 8 PR
TL/TT	TT
Brand	BKT
Tread pattern	TR 135
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	33,10
Recommended rim size	W11
Permitted rim size	W9, 9, W10, 11
Maximum air pressure [bar].	2,10
Section width (mm)	325
Outer diameter of tyre [mm].	1075
Stat. radius (SLR) [mm]	500
Rolling circumference [mm].	3160
Tread depth (mm)	34,0
Number of lugs	16x2
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
116 A6	1250	30		2,10	
112 A8	1120	40		2,10	