

TYRES

Product group	Tyres
Item number	15722080
Valid tyre size	9.5 - 22
LI / SI / PR	104 A6 / 100 A8, 6 PR
TL/TT	TT
Brand	BKT
Tread pattern	TR 144



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- Agricultural bias tyre for smaller tractors.
- Wide lug spaces for good traction on wet surfaces.
- Angled lugs in the centre for better ride comfort.

Technical Informations

Item number	15722080
EAN	8903094004744
Valid tyre size	9.5 - 22
LI / SI / PR	104 A6 / 100 A8, 6 PR
TL/TT	TT
Brand	BKT
Tread pattern	TR 144
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	24,20
Recommended rim size	7
Permitted rim size	8
Maximum air pressure [bar].	2,20
Section width (mm)	235
Outer diameter of tyre [mm].	1000
Stat. radius (SLR) [mm]	464
Rolling circumference [mm].	3008
Tread depth (mm)	28,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
104 A6	900	30		2,20	
100 A8	800	40		2,20	