

## TYRES

Product group	Tyres
Item number	15722096
Valid tyre size	9.5 - 24
LI / SI / PR	116 A6 / 112 A8, 10 PR
TL/TT	TT
Brand	BKT
Tread pattern	TR 135



Bohnenkamp  
■ ■ ● Moving Professionals



## Notes and features

- The BKT TR 135 is an agricultural bias tyre for soil tillage and spraying applications.
- Some sizes and versions are suitable for use on excavators, trailers or harvesters.
- The double angled lugs provide excellent traction.
- The tyre offers good self-cleaning properties and excellent stability, even on difficult ground conditions.
- The lugs overlapping in the tread centre ensure comfortable handling on the road.

## Technical Informations

Item number	15722096
EAN	8903094032648
Valid tyre size	9.5 - 24
LI / SI / PR	116 A6 / 112 A8, 10 PR
TL/TT	TT
Brand	BKT
Tread pattern	TR 135
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	28,00
Recommended rim size	W8
Permitted rim size	W7
Maximum air pressure [bar].	3,50
Section width (mm)	241
Outer diameter of tyre [mm].	1060
Stat. radius (SLR) [mm]	502
Rolling circumference [mm].	3234
Tread depth (mm)	30,5
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
116 A6	1250	30		3,50	
112 A8	1120	40		3,50	