

TYRES

Product group	Tyres
Item number	15722100
Valid tyre size	11.2 - 24
LI / SI / PR	116 A6 / 112 A8, 8 PR
TL/TT	TT
Brand	BKT
Tread pattern	TR 135



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- The BKT TR 135 is an agricultural bias tyre for soil tillage and spraying applications.
- Some sizes and versions are suitable for use on excavators, trailers or harvesters.
- The double angled lugs provide excellent traction.
- The tyre offers good self-cleaning properties and excellent stability, even on difficult ground conditions.
- The lugs overlapping in the tread centre ensure comfortable handling on the road.

Technical Informations

Item number	15722100
EAN	8903094003044
Valid tyre size	11.2 - 24
LI / SI / PR	116 A6 / 112 A8, 8 PR
TL/TT	TT
Brand	BKT
Tread pattern	TR 135
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	31,53
Recommended rim size	W10
Permitted rim size	W9
Maximum air pressure [bar].	2,40
Section width (mm)	284
Outer diameter of tyre [mm].	1105
Stat. radius (SLR) [mm]	517
Rolling circumference [mm].	3399
Tread depth (mm)	33,0
Number of lugs	18x2
Tyre capacity 75% [ltr.]	109
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
116 A6	1250	30		2,40	
112 A8	1120	40		2,40	