

TYRES

Product group	Tyres
Item number	15722135
Valid tyre size	12.4 - 24
LI / SI / PR	121 A6 / 118 A8, 8 PR
TL/TT	TT
Brand	BKT
Tread pattern	TR 135



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- The BKT TR 135 is an agricultural bias tyre for soil tillage and spraying applications.
- Some sizes and versions are suitable for use on excavators, trailers or harvesters.
- The double angled lugs provide excellent traction.
- The tyre offers good self-cleaning properties and excellent stability, even on difficult ground conditions.
- The lugs overlapping in the tread centre ensure comfortable handling on the road.

Technical Informations

Item number	15722135
EAN	8903094003129
Valid tyre size	12.4 - 24
LI / SI / PR	121 A6 / 118 A8, 8 PR
TL/TT	TT
Brand	BKT
Tread pattern	TR 135
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	39,59
Recommended rim size	W11
Permitted rim size	W9, W10
Maximum air pressure [bar].	2,30
Section width (mm)	315
Outer diameter of tyre [mm].	1160
Stat. radius (SLR) [mm]	543
Rolling circumference [mm].	3573
Tread depth (mm)	34,0
Number of lugs	18x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
121 A6	1450	30		2,30	
118 A8	1320	40		2,30	