

## TYRES

Product group	Tyres
Item number	15722171
Valid tyre size	13.6 - 24
LI / SI / PR	130 A6 / 126 A8, 12 PR
TL/TT	TT
Brand	BKT
Tread pattern	TR 135



Bohnenkamp  
Moving Professionals



## Notes and features

- The BKT TR 135 is an agricultural bias tyre for soil tillage and spraying applications.
- Some sizes and versions are suitable for use on excavators, trailers or harvesters.
- The double angled lugs provide excellent traction.
- The tyre offers good self-cleaning properties and excellent stability, even on difficult ground conditions.
- The lugs overlapping in the tread centre ensure comfortable handling on the road.

## Technical Informations

Item number	15722171
EAN	8903094029938
Valid tyre size	13.6 - 24
LI / SI / PR	130 A6 / 126 A8, 12 PR
TL/TT	TT
Brand	BKT
Tread pattern	TR 135
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	50,23
Recommended rim size	W12
Permitted rim size	W11
Maximum air pressure [bar].	2,90
Section width (mm)	355
Outer diameter of tyre [mm].	1220
Stat. radius (SLR) [mm]	562
Rolling circumference [mm].	3698
Tread depth (mm)	35,5
Number of lugs	17x2
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
130 A6	1900	30		2,90	
126 A8	1700	40		5,90	