

TYRES

Product group	Tyres
Item number	15722185
Valid tyre size	14.9 - 24
LI / SI / PR	128 A6 / 124 A8, 8 PR
TL/TT	TL
Brand	BKT
Tread pattern	TR 391



Notes and features

- Industrial bias tyre with block tread pattern for varying uses, e.g. road construction on drum compactors, on industrial tractors or in agriculture and landscape management on different machines and heavy equipment.
- Wide tread pattern block and rounded shoulders guarantee optimal soil protection and good surface contact for good propulsion.
- Increased tread pattern depth and reinforced casing for a longer service life.

Technical Informations

Item number	15722185
EAN	8903094005277
Valid tyre size	14.9 - 24
LI / SI / PR	128 A6 / 124 A8, 8 PR
TL/TT	TL
Brand	BKT
Tread pattern	TR 391
TRA Code	R3
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	58,24
Recommended rim size	DW13
Permitted rim size	W12
Maximum air pressure [bar].	1,80
Section width (mm)	405
Outer diameter of tyre [mm].	1270
Stat. radius (SLR) [mm]	574
Rolling circumference [mm].	3805
Tread depth (mm)	19,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
128 A6	1800	30		1,80	
124 A8	1600	40		1,80	