

TYRES

Product group	Tyres
Item number	15722191
Valid tyre size	16.9 - 24
LI / SI / PR	140 A6, 12 PR
TL/TT	TT
Brand	BKT
Tread pattern	TR 135



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- The BKT TR 135 is an agricultural bias tyre for soil tillage and spraying applications.
- Some sizes and versions are suitable for use on excavators, trailers or harvesters.
- The double angled lugs provide excellent traction.
- The tyre offers good self-cleaning properties and excellent stability, even on difficult ground conditions.
- The lugs overlapping in the tread centre ensure comfortable handling on the road.

Technical Informations

Item number	15722191
EAN	8903094061815
Valid tyre size	16.9 - 24
LI / SI / PR	140 A6, 12 PR
TL/TT	TT
Brand	BKT
Tread pattern	TR 135
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	74,54
Recommended rim size	W15L
Permitted rim size	W14L
Maximum air pressure [bar].	2,40
Section width (mm)	429
Outer diameter of tyre [mm].	1335
Stat. radius (SLR) [mm]	613
Speed Radius Index (SRI)	575
Rolling circumference [mm].	3925
Tread depth (mm)	37,5
Number of lugs	17x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
140 A6	2500	30		2,40	