

TYRES

Product group	Tyres	
Item number	15722193	
Valid tyre size	23.5 - 25	
LI / SI / PR	191 A2, 20 PR	
TL/TT	TL	
Brand	BKT	
Tread pattern	Harvester Special	





Notes and features

- The BKT Harvester Special was specially developed for use on wheel loaders.
- Dual angled lugs offer excellent traction in the field and riding comfort on the road.
- The large contact area ensures very high tyre stability.
- The strong carcass together with a cut- and break resistant rubber compound guarantee a long service life.



Technical Informations

Item number	15722193
EAN	8903094065882
Valid tyre size	23.5 - 25
LI / SI / PR	191 A2, 20 PR
TL/TT	TL
Brand	BKT
Tread pattern	Harvester Special
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	227,68
Recommended rim size	19.50/2.5
Maximum air pressure [bar].	3,75
Section width (mm)	615
Outer diameter of tyre [mm].	1665
Stat. radius (SLR) [mm]	715
Rolling circumference [mm].	5058
Tread depth (mm)	46,5
Number of lugs	21x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
191 A2	10900	10		3,75	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.