# Bohnenkamp Moving Professionals

18.11.2024

### **TYRES**

| Product group   | Tyres                 |  |
|-----------------|-----------------------|--|
| Item number     | 15722195              |  |
| Valid tyre size | 13.6 - 26             |  |
| LI / SI / PR    | 120 A6 / 116 A8, 6 PR |  |
| TL/TT           | тт                    |  |
| Brand           | ВКТ                   |  |
| Tread pattern   | TR 171                |  |



#### Notes and features

- Suitable for wet surfaces.
- Extra high lugs for long service life.

• Very good traction and self-cleaning.

## Bohnenkamp Moving Professionals

### **Technical Informations**

| Item number                  | 15722195              |
|------------------------------|-----------------------|
| EAN                          | 8903094025633         |
| Valid tyre size              | 13.6 - 26             |
| LI / SI / PR                 | 120 A6 / 116 A8, 6 PR |
| TL/TT                        | ТТ                    |
| Brand                        | ВКТ                   |
| Tread pattern                | TR 171                |
| Antistatic                   | No                    |
| Tyre colour                  | Black                 |
| ECE regulation number        | ECE 106               |
| Nettogewicht [kg] (gültig)   | 62,41                 |
| Recommended rim size         | W12                   |
| Permitted rim size           | W11                   |
| Maximum air pressure [bar].  | 1,60                  |
| Section width (mm)           | 340                   |
| Outer diameter of tyre [mm]. | 1270                  |
| Stat. radius (SLR) [mm]      | 580                   |
| Rolling circumference [mm].  | 3774                  |
| Tread depth (mm)             | 54,0                  |
| Number of lugs               | 15x2                  |
| E-Ready                      | No                    |

## Load capacity

| Index  | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure<br>[bar] | Load variant |
|--------|--------------------|--------------|---------------|-----------------------------|--------------|
| 120 A6 | 1400               | 30           |               | 1,60                        |              |
| 116 A8 | 1250               | 40           |               | 1,60                        |              |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.