

TYRES

Product group	Tyres
Item number	15722200
Valid tyre size	14.9 - 26
LI / SI / PR	129 A6 / 125 A8, 8 PR
TL/TT	TT
Brand	BKT
Tread pattern	TR 135



Bohnenkamp
■ ■ ● Moving Professionals

BKT
GROWING TOGETHER

Notes and features

- The BKT TR 135 is an agricultural bias tyre for soil tillage and spraying applications.
- Some sizes and versions are suitable for use on excavators, trailers or harvesters.
- The double angled lugs provide excellent traction.
- The tyre offers good self-cleaning properties and excellent stability, even on difficult ground conditions.
- The lugs overlapping in the tread centre ensure comfortable handling on the road.

Technical Informations

Item number	15722200
EAN	8903094028382
Valid tyre size	14.9 - 26
LI / SI / PR	129 A6 / 125 A8, 8 PR
TL/TT	TT
Brand	BKT
Tread pattern	TR 135
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	57,69
Recommended rim size	W13
Permitted rim size	W11, W12
Maximum air pressure [bar].	1,80
Section width (mm)	375
Outer diameter of tyre [mm].	1315
Stat. radius (SLR) [mm]	608
Rolling circumference [mm].	3863
Tread depth (mm)	36,0
Number of lugs	17x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
129 A6	1850	30		1,80	
125 A8	1650	40		1,80	