Bohnenkamp Moving Professionals

TYRES

Product group	Tyres	
Item number	15722210	
Valid tyre size	18.4 - 26	
valid tyle size	10.4 - 20	
LI / SI / PR	146 A6, 12 PR	
	140710, 12111	
TL/TT	тт	
Brand	BKT	
Tread pattern	AS 2001	



Notes and features

- Suitable for agricultural work, backhoe loaders.
- Robust tyre with high number of plies.

• Reinforced casing.

Bohnenkamp Moving Professionals

Technical Informations

Item number	15722210
EAN	8903094002795
Valid tyre size	18.4 - 26
LI / SI / PR	146 A6, 12 PR
TL/TT	Π
Brand	ВКТ
Tread pattern	AS 2001
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	88,79
Recommended rim size	W16L
Permitted rim size	W15L
Maximum air pressure [bar].	2,30
Section width (mm)	467
Outer diameter of tyre [mm].	1475
Stat. radius (SLR) [mm]	650
Rolling circumference [mm].	4250
Tread depth (mm)	38,0
Number of lugs	19x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
146 A6	3000	30		2,30	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.